



PRODUCT NAME Diesel Fuel Cond./w Anti- Gel #-MSDS2025
 PRODUCT-2025

(Page 1 of 2)

1. INGREDIENTS	CAS #	ACGIH TLV	OSHA PEL	OTHER LIMITS	%
Petroleum Distillate	68476-34-6		400 ppm	100 ppm	23-28
2-Butoxy Ethanol	111-76-2	25 ppm	25 ppm	(skin)	4-7
Xylene	1330-20-7	100 ppm	100 ppm		30-40
Tetrahydronaphthalene	119-64-2	NA	NA		4-6
Copolymer Resin	24937-78-8	NA	NA		20-26
Detergent	-	NA	NA		3-6

2. PHYSICAL DATA :

Specific Gravity : 0.897
 Vapor Pressure : ND
 % Volatile : 100
 Boiling Point : ND
 Evaporation Rate : NA
 Freezing Point : ND
 Vapor Density : NA
 Appearance and Odor: pH: NA
 A light amber, clear liquid.

Solubility : Negligible in water- dissolves in most organic solvents

3. FIRE AND EXPLOSION DATA

Flashpoint : 93 F Method : TCC
 Flammable Limits : ND LEL: UEL:
 Extinguishing Media : CO2, dry chemical, foam
 Unusual Hazards : Treat as an oil fire.

4. REACTIVITY AND STABILITY

Stability : Stable
 Hazardous decomposition products : CO2, Carbon Monoxide (fire)

Materials to avoid : Strong oxidizing agents.

5. PROTECTION INFORMATION

Ventilation : Adequate ventilation to maintain vapor conc. below the TLV.

Respiratory : Use self contained breathing apparatus above the TLV.

Gloves : Solvent Resistant Eye & Face : Safety glasses
 Other Protective Equipment: Oil resistant aprons, boots, etc. should be worn if possibility of body contact exists.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME : Diesel Fuel Cond./w Anti- Gel #-MSDS2025
PRODUCTS-2025

MANUFACTURED BY : CRC INDUSTRIES, INC.
885 LOUIS DRIVE, WARMINSTER, PA. 18974

PHONE (215) 674-4300

(Page 2 of 2)

6. HEALTH HAZARD DATA

Primary Routes of Entry : Inhalation, Skin

Signs and Symptoms of Exposure

1. Acute Overexposure:

May cause burning, irritation of eyes. Skin contact will cause dryness. Inhalation of mist may cause breathing problems and irritation of resp. tract. Vapors may cause headaches, nausea

2. Chronic overexposure: Prolonged overexposure to skin may cause development of dermatitis.

Medical Conditions Generally Aggravated by Exposure : NA

Chemical Listed as Carcinogen : No National Toxicology Program
or Potential Carcinogen : No IARC Monographs
: No OSHA

Emergency and First Aid Procedures : (If symptoms persist, call a physician)

- 1. Inhalation : Remove to fresh air. Apply artificial respiration if necessary.
- 2. Eyes : Flush for 15 minutes with large amounts of water.
- 3. Skin : Remove contaminated clothing. Wash exposed area with soap and water.
- 4. Ingestion : DO NOT induce vomiting. Call a physician.

7. SPILL OR LEAK PROCEDURES

Precautions to be taken : Store in a cool, dry area.
in Handling and Storage

Steps to be taken in case : Ventilate area. Remove sources of ignition. Dike
Material is released or area and absorb with sand or other absorbent.
spilled Scrape up and place in drums.

Waste Disposal : All used and unused Product should be disposed of in
conformance with local, state and federal regulations.

8. SPECIAL PRECAUTIONS AND USE DIRECTIONS :

Keep containers closed when not in use. Spills should be kept out of streams or water supply.

9. NFPA HAZARD RATINGS Health:2 Flammability:3 Reactivity:0

10. SARA Information

This product contains the following chemicals that are subject to release reporting under Section 313 of SARA Title III.

Chemical Name	CAS-#	Percent
2-Butoxy Ethanol	111-76-2	4-7
Xylene	1330-20-7	30-40

PREPARED BY: Jon Brown

ORIGINAL DATE or DATE OF REVISION: 12/17/93