Material Safety Data Sheet

GPG-0000 Gripper Interior/Exterior Primer - White

1 . Product and company identification

Product name : GPG-0000 Gripper Interior/Exterior Primer - White

Manufacturer : PPG Architectural Finishes, Inc.
15885 W. Sprague Road
Strongsville, OH 44136

Validation date : **2014-02-12.**

Print date : 2014-02-12.

Responsible name : Product Stewardship, Regulatory Affairs & Labeling

In case of emergency : 1-800-545-2643

2. Hazards identification

Emergency overview

Physical state : Liquid.

Signal word : WARNING!

Hazard statements
CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY BE HARMFUL IF SWALLOWED. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA. POSSIBLE CANCER HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE CANCER, BASED ON ANIMAL DATA.

Precautionary measures : Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Do not eat, drink or smoke when using this product. Avoid contact with eyes, skin and clothing. Keep container tightly closed. Use personal protective equipment as required. Wash thoroughly after handling.

Potential acute health effects

Inhalation : Irritating to respiratory system.

Ingestion : Harmful if swallowed.

Skin : Irritating to skin.

Eyes : Irritating to eyes.

Potential chronic health effects

Chronic effects : Contains material that may cause target organ damage, based on animal data.

Carcinogenicity : Contains material which may cause cancer, based on animal data. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Target organs : Contains material which may cause damage to the following organs: lungs, upper respiratory tract, skin, eyes.

Over-exposure signs/symptoms

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing

Ingestion : No specific data.

Skin : Adverse symptoms may include the following:
irritation
redness

2. Hazards identification

Eyes : Adverse symptoms may include the following:
pain or irritation
watering
redness

See toxicological information (Section 11)

3. Composition/information on ingredients

Name	CAS number	%
Acrylic (co)polymer, waterborne		10-<30
titanium dioxide	13463-67-7	10-<30
Nepheline syenite	37244-96-5	10-<30
Limestone	1317-65-3	10-<30
isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	25265-77-4	1-<5
Palygorskite ([Mg(Al0.5-1Fe0-0.5)]Si4(OH)O10.4H2O)	12174-11-7	0.1-<1.0
water	7732-18-5	30-<60
Vinyl acetate/butyl acrylate copolymer	25067-01-0	10-<30

4. First aid measures

Eye contact : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

Skin contact : In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

Inhalation : Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

Ingestion : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

5. Fire-fighting measures

Flammability of the product : In a fire or if heated, a pressure increase will occur and the container may burst.

Extinguishing media

Suitable : Use an extinguishing agent suitable for the surrounding fire.

Not suitable : None known.

Special exposure hazards : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container.

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7. Handling and storage

Handling : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Keep out of the reach of children.

Storage : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Keep from freezing.

8. Exposure controls/personal protection

Ingredient	Exposure limits
titanium dioxide	**OSHA PEL (United States, 6/2010).** TWA: 15 mg/m³ 8 hour(s). Form: Total dust **OSHA PEL 1989 (United States, 3/1989).** TWA: 10 mg/m³ 8 hour(s). Form: Total dust **ACGIH TLV (United States, 1/2011). Notes: Substance identified by other sources as a suspected or confirmed human carcinogen. 1996 Adoption Substances for which the TLV is higher than the OSHA Permissible Exposure Limit (PEL) and/or the NIOSH Recommended Exposure Limit (REL). See CFR 58(124) :36338-33351, June 30, 1993, for revised OSHA PEL. Refers to Appendix A -- Carcinogens.** TWA: 10 mg/m³ 8 hour(s).
Limestone	**NIOSH REL (United States, 6/2009).** TWA: 5 mg/m³ 10 hour(s). Form: Respirable fraction TWA: 10 mg/m³ 10 hour(s). Form: Total **OSHA PEL (United States, 6/2010).**

8. Exposure controls/personal protection

	TWA: 5 mg/m³ 8 hour(s). Form: Respirable fraction TWA: 15 mg/m³ 8 hour(s). Form: Total dust **OSHA PEL 1989 (United States, 3/1989).** TWA: 5 mg/m³ 8 hour(s). Form: Respirable fraction TWA: 15 mg/m³ 8 hour(s). Form: Total dust

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Respiratory : A NIOSH-approved, air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where air-purifying respirators may not provide adequate protection.

Hands : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eyes : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Skin : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

Physical state : Liquid.

Flash point : Closed cup: 999°C (1830.2°F)

Auto-ignition temperature : Not available.

Flammable limits : Not available.

Color : Not available.

Odor : not available

pH : Not available.

Boiling/condensation point : Not available.

Melting/freezing point : 0°C (32°F)

Specific gravity : 1.34

Density (lbs/gal) : 11.182

Vapor pressure : Not available.

Vapor density : Not available.

Volatility : 53.82% (v/v), 40.76% (w/w)

9. Physical and chemical properties

Viscosity : Dynamic: 2050 mPa·s (2050 cP)

Dispersibility properties : Easily dispersible in the following materials: cold water.

Solubility : Easily soluble in the following materials: cold water.

10. Stability and reactivity

Chemical stability : The product is stable.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	LD50 Oral	Rat	3200 mg/kg	-

Conclusion/Summary : Not available.

Chronic toxicity

Conclusion/Summary : Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
titanium dioxide	Skin - Mild irritant	Human	-	72 hours 300 Micrograms Intermittent	-

Conclusion/Summary : Not available.

Sensitizer

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
titanium dioxide	A4	2B	-	+	-	-
Palygorskite ([Mg(Al0.5-1Fe0-0.5)]Si4(OH)O10.4H2O)	-	2B	-	-	-	-

Mutagenicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

12. Ecological information

Ecotoxicity : No known significant effects or critical hazards.

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute EC50 5.83 mg/L Fresh water	Algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours
	Acute LC50 5.5 ppm Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling) - <24 hours	48 hours
	Acute LC50 >1000000 ug/L Marine water	Fish - Fundulus heteroclitus	96 hours

Conclusion/Summary : Not available.

Persistence/degradability

Conclusion/Summary : Not available.

13. Disposal considerations

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	Not available.	Not available.	Not available.	-		-
IMDG Class	Not available.	Not available.	Not available.	-		-

PG* : Packing group

15. Regulatory information

U.S. Federal regulations : **United States inventory (TSCA 8b)**: All components are listed or exempted.

SARA 302/304/311/312 extremely hazardous substances: No components were found.

SARA 302/304 emergency planning and notification: No components were found.

SARA 302/304/311/312 hazardous chemicals: titanium dioxide; Limestone

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: titanium dioxide: Immediate (acute) health hazard; Limestone: Immediate (acute) health hazard

State regulations

Massachusetts : The following components are listed: TITANIUM DIOXIDE; CALCIUM CARBONATE

New York : None of the components are listed.

New Jersey : The following components are listed: TITANIUM DIOXIDE; TITANIUM OXIDE (TiO2); CALCIUM CARBONATE; LIMESTONE

Pennsylvania : The following components are listed: TITANIUM OXIDE (TIO2); LIMESTONE

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

International regulations

Canada inventory : Not determined.

16. Other information

Hazardous Material Information System (U.S.A.) :



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

Prepared by : Product Stewardship, Regulatory Affairs & Labeling

Notice to reader

The information contained herein is based on data available at the time of preparation of this data sheet and which PPG Architectural Finishes, Inc. believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. PPG Architectural Finishes, Inc. shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

Complies with OSHA Hazard Communication Standard 29CFR1910.1200.