

SAFETY DATA SHEET

Version 4.15
Revision Date 10/20/2017
Print Date 11/20/2017

1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name : 2-Methoxyethanol

Product Number : 284467

Brand : Sigma-Aldrich

Index-No. : 603-011-00-4

CAS-No. : 109-86-4

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich
3050 Spruce Street
SAINT LOUIS MO 63103
USA

Telephone : +1 800-325-5832

Fax : +1 800-325-5052

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 3), H226

Acute toxicity, Oral (Category 4), H302

Acute toxicity, Inhalation (Category 4), H332

Acute toxicity, Dermal (Category 4), H312

Reproductive toxicity (Category 1B), H360

Specific target organ toxicity - single exposure (Category 1), H370

Specific target organ toxicity - repeated exposure (Category 2), H373

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)

H226 : Flammable liquid and vapour.

H302 + H312 + H332 : Harmful if swallowed, in contact with skin or if inhaled.

H360 : May damage fertility or the unborn child.

H370 : Causes damage to organs.

H373 : May cause damage to organs through prolonged or repeated exposure.

Precautionary statement(s)

P201 : Obtain special instructions before use.

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P307 + P311	IF exposed: Call a POISON CENTER or doctor/ physician.
P363	Wash contaminated clothing before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Synonyms	: Methyl Cellosolve Methyl glycol Ethylene glycol monomethyl ether
Formula	: C ₃ H ₈ O ₂
Molecular weight	: 76.09 g/mol
CAS-No.	: 109-86-4
EC-No.	: 203-713-7
Index-No.	: 603-011-00-4
Registration number	: 01-2119494721-33-XXXX

Hazardous components

Component	Classification	Concentration
2-Methoxyethanol	Flam. Liq. 3; Acute Tox. 4; Repr. 1B; STOT SE 1; STOT RE 2; H226, H302 + H312 + H332, H360, H370, H373	90 - 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. FIREFIGHTING MEASURES**5.1 Extinguishing media****Suitable extinguishing media**

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

No data available

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE**7.1 Precautions for safe handling**

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
2-Methoxyethanol	109-86-4	TWA	0.100000 ppm 0.300000 mg/m3	USA. NIOSH Recommended Exposure Limits
	Remarks	Potential for dermal absorption		
		TWA	0.100000 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Hematologic effects Reproductive effects Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption		
		TWA	0.1 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Hematologic effects Reproductive effects Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption		
		TWA	25.000000 ppm 80.000000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		Skin designation The value in mg/m3 is approximate.		
		TWA	25 ppm 80 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		Skin designation The value in mg/m3 is approximate.		
		TWA	25 ppm 80 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		Skin notation		
		TWA	0.1 ppm 0.3 mg/m3	USA. NIOSH Recommended Exposure Limits
		Potential for dermal absorption		
		PEL	5 ppm 16 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		Skin		

Biological occupational exposure limits

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
2-Methoxyethanol	109-86-4	2-Methoxyacetic acid	1mg/g Creatinine	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift at end of workweek			

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm

Break through time: 480 min

Material tested: Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact

Material: Nature latex/chloroprene

Minimum layer thickness: 0.6 mm

Break through time: 35 min

Material tested: Lapren® (KCL 706 / Aldrich Z677558, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

- | | |
|--|---|
| a) Appearance | Form: clear, liquid
Colour: colourless |
| b) Odour | ether-like |
| c) Odour Threshold | No data available |
| d) pH | 5.0 - 7.0 at 25 °C (77 °F) |
| e) Melting point/freezing point | Melting point/range: -85 °C (-121 °F) - lit. |
| f) Initial boiling point and boiling range | 124 - 125 °C (255 - 257 °F) - lit. |
| g) Flash point | 40 °C (104 °F) - closed cup |
| h) Evaporation rate | No data available |
| i) Flammability (solid, gas) | No data available |
| j) Upper/lower flammability or | Upper explosion limit: 24.5 %(V)
Lower explosion limit: 2.5 %(V) |

explosive limits

- | | |
|---|---|
| k) Vapour pressure | 10 hPa (8 mmHg) at 20 °C (68 °F) |
| l) Vapour density | 2.63 - (Air = 1.0) |
| m) Relative density | 0.965 g/cm ³ at 25 °C (77 °F) |
| n) Water solubility | soluble |
| o) Partition coefficient: n-octanol/water | log Pow: -0.8 |
| p) Auto-ignition temperature | No data available |
| q) Decomposition temperature | 204 - 232 °C (399 - 450 °F) - |
| r) Viscosity | 1.6 mm ² /s at 20 °C (68 °F) - |
| s) Explosive properties | Not explosive |
| t) Oxidizing properties | No data available |

9.2 Other safety information

Relative vapour density 2.63 - (Air = 1.0)

10. STABILITY AND REACTIVITY

10.1 Reactivity

Vapours may form explosive mixture with air.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Aluminum, Magnesium, Alkalis, Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male - 2,257 mg/kg
(OECD Test Guideline 401)

LC50 Inhalation - Rat - 4 h - 12.4 - 17.8 mg/l

LD50 Dermal - Rabbit - 1,280 mg/kg

LD50 Intraperitoneal - Rat - 2,500 mg/kg

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation

(Directive 67/548/EEC, Annex V, B.4.)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Mild eye irritation - 24 h

(OECD Test Guideline 405)

Respiratory or skin sensitisation

Maximisation Test - Guinea pig

Result: Does not cause skin sensitisation.

Germ cell mutagenicity

In vitro mammalian cell gene mutation test

Chinese hamster ovary cells

Result: negative

OECD Test Guideline 475

Mouse - male

Result: negative

Carcinogenicity

No data available

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

May cause congenital malformation in the fetus.

Presumed human reproductive toxicant

May cause reproductive disorders.

Developmental Toxicity - Rat - Dermal

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure. - thymus

Oral - Testes, thymus

Aspiration hazard

No data available

Additional Information

Repeated dose toxicity Rat - male - Oral - NOAEL : < 71 mg/kg

RTECS: KL5775000

Effects due to ingestion may include:, Changes in the blood count, Headache, Central nervous system depression, Ingestion of large amounts may cause:, Damage of the:, Liver, Kidney, Central nervous system

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity to fish static test LC50 - *Lepomis macrochirus* (Bluegill) - 10,000 mg/l - 96 h (OECD Test Guideline 203)

Toxicity to daphnia and other aquatic invertebrates semi-static test EC50 - *Daphnia magna* (Water flea) - 27,000 mg/l - 48 h

Toxicity to algae static test EC50 - Pseudokirchneriella subcapitata - 25,500 mg/l - 72 h

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 20 d
Result: 88 % - Readily biodegradable.

12.3 Bioaccumulative potential

No bioaccumulation is to be expected (log Pow <= 4).

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 1188 Class: 3 Packing group: III
Proper shipping name: Ethylene glycol monomethyl ether
Reportable Quantity (RQ):
Poison Inhalation Hazard: No

IMDG

UN number: 1188 Class: 3 Packing group: III EMS-No: F-E, S-D
Proper shipping name: ETHYLENE GLYCOL MONOMETHYL ETHER
Marine pollutant: yes

IATA

UN number: 1188 Class: 3 Packing group: III
Proper shipping name: Ethylene glycol monomethyl ether

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
2-Methoxyethanol	109-86-4	2007-07-01

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

	CAS-No.	Revision Date
2-Methoxyethanol	109-86-4	2007-07-01

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
2-Methoxyethanol	109-86-4	2007-07-01

New Jersey Right To Know Components

2-Methoxyethanol

CAS-No.
109-86-4

Revision Date
2007-07-01

California Prop. 65 Components

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

2-Methoxyethanol

CAS-No.
109-86-4

Revision Date
2009-02-01

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Acute Tox.	Acute toxicity
Flam. Liq.	Flammable liquids
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H302 + H312 + H332	Harmful if swallowed, in contact with skin or if inhaled.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H360	May damage fertility or the unborn child.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.

HMIS Rating

Health hazard:	1
Chronic Health Hazard:	*
Flammability:	2
Physical Hazard	0

NFPA Rating

Health hazard:	1
Fire Hazard:	2
Reactivity Hazard:	0

Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Preparation Information

Sigma-Aldrich Corporation
Product Safety – Americas Region
1-800-521-8956

Version: 4.15

Revision Date: 10/20/2017

Print Date: 11/20/2017